



EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
03.12.1997 Bulletin 1997/49

(51) Int. Cl.⁶: **B66B 11/00**, B66B 11/08,
B66B 11/04

(21) Application number: 94109887.3

(22) Date of filing: 27.06.1994

(54) **Traction sheave elevator**

Antriebsscheibenaufzug

Ascenseur à poulie de traction

(84) Designated Contracting States:
**AT BE CH DE DK ES FR GB GR IE IT LI LU MC NL
PT SE**
Designated Extension States:
SI

(30) Priority: 14.04.1994 FI 941719
28.06.1993 FI 932977

(43) Date of publication of application:
04.01.1995 Bulletin 1995/01

(60) Divisional application:
96115656.9 / 0 784 030
96115655.1 / 0 779 233

(73) Proprietor: **KONE OY**
00330 Helsinki 33 (FI)

(72) Inventors:
• Aulanko, Esko
SF-04230 Kerava (FI)
• Mustalahti, Jorma
SF-05620 Hyvinkää (FI)
• Hakala, Harri
SF-05830 Hyvinkää (FI)

(74) Representative:
Zipse + Habersack
Wotanstrasse 64
80639 München (DE)

(56) References cited:
FR-A- 1 451 792

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

The present invention relates to a traction sheave elevator as defined in the preamble of claim 1.

One of the objectives in elevator development work has been an efficient and economic utilization of building space. In conventional traction-sheave driven elevators, the elevator machine room or other space reserved for the drive machinery takes up a considerable portion of the building space needed for the elevator. The problem is not only the volume of the building space needed for the drive machinery, but also its location in the building. There are numerous solutions to the placement of the machine room, but they generally significantly restrict the design of the building at least in respect of space utilization or appearance. For example, a machine room placed on the roof of a building can be felt to be a flaw of appearance. Being a special space, the machine room generally involves increased building costs.

In prior art, hydraulic elevators are relatively advantageous with respect to utilization of space, and they often allow the entire drive machine to be placed in the elevator shaft. However, hydraulic elevators are only applicable in cases where the lifting height is one floor or at most a few floors. In practice, hydraulic elevators cannot be constructed for very large heights.

JP utility model publication 4-50297 discloses a machineromless rucksack-type elevator (small type elevator) wherein the drive unit is mounted on the heads of the guide rails. However, as the base surface of the drive machine unit is rather large, a large distance has to be provided between the cabin path and the shaft wall. This necessitates a larger base surface of the elevator shaft and therefore higher investments with respect to the building costs.

To meet the need to achieve a reliable elevator which is advantageous in respect of economy and space utilization and for which the space requirement in the building, irrespective of the hoisting height, is substantially limited to the space required by the elevator car and counterweight on their paths including the safety distances and the space needed for the hoisting ropes, and in which the above-mentioned drawbacks can be avoided, a new type of traction sheave elevator is presented as an invention. The traction sheave elevator of the invention is characterized by what is presented in the characterizing part of claim 1. Other embodiments of the invention are characterized by the features presented in the other claims.

The advantages which can be achieved by applying the present invention include the following:

- The traction sheave elevator of the invention allows an obvious space saving to be achieved in the building because no separate machine room is needed.
- Efficient utilization of the cross-sectional area of the elevator shaft.

- Advantages in manufacture and installation because the system has fewer discrete components than conventional traction sheave elevators.
- In elevators implemented using the invention, the ropes meet the traction sheave and diverting pulleys from a direction aligned with the rope grooves of the diverting pulleys, a circumstance which reduces rope wear.
- In elevators implemented using the invention, it is not difficult to achieve a centric suspension of the elevator car and counterweight and therefore a substantial reduction of the supporting forces applied to the guide rails. This permits the use of lighter guide rails as well as lighter elevator and counterweight guides.
- The design of the elevator allows the elevator to be implemented using other than rucksack-type suspension, permitting the area of application of the elevator solution to be more easily expanded to cover large loads and high speeds.
- The elevator car and safety gear frame can be designed without problems using the solutions applied in conventional elevators with a machine room, which are lighter and simpler than those used in rucksack-type elevators.
- In elevators implemented according to the invention, the supporting forces applied to the guide rails are of a moderate order.

In the following, the invention is described in detail by the aid of some of its embodiments by referring to the attached drawings, in which

- Fig. 1 presents a traction sheave elevator according to the invention in diagrammatic form, and
- Fig. 2 presents a diagram illustrating the placement of an elevator according to the invention in an elevator shaft in top view,
- Fig. 3 presents another traction sheave elevator according to the invention in diagrammatic form,
- Fig. 4a presents a diagram illustrating the placement of an elevator according to the invention in an elevator shaft in lateral view,
- Fig. 4b shows the elevator of fig 2a in top view,
- Fig. 5 presents a cross-section of a hoisting machine unit applied in the invention, and
- Fig. 6 presents a cross-section of another hoisting machine unit applied in the invention.

A traction sheave elevator according to the invention is presented in Fig. 1 in diagrammatic form. The elevator car 1 and counterweight 2 are suspended on the hoisting ropes 3 of the elevator. The hoisting ropes 3 preferably support the elevator car 1 substantially centrally or symmetrically with respect to the vertical line passing via the centre of gravity of the elevator car 1. Similarly, the suspension of the counterweight 2 is pref-

erably substantially centric or symmetrical relative to the vertical line going through the centre of gravity of the counterweight. In Fig. 1, the elevator car 1 is supported by the hoisting ropes 3 by means of diverting pulleys 4,5 provided with rope grooves, and the counterweight 2 is supported by a grooved diverting pulley 9. The diverting pulleys 4 and 5 preferably rotate substantially in the same plane. The hoisting ropes 3 usually consist of several ropes placed side by side, usually at least three ropes. The drive machine unit 6 of the elevator with a traction sheave 7 engaging the hoisting ropes 3 is placed in the top part of the elevator shaft.

The elevator car 1 and the counterweight 2 travel in the elevator shaft along elevator and counterweight guide rails 10,11 which guide them. The elevator and counterweight guides are not shown in the figure.

In Fig. 1, the hoisting ropes 3 run as follows: One end of the hoisting ropes is fixed to an anchorage 13 above the path of the counterweight 2 at the top part of the shaft. From the anchorage 13, the ropes go downwards until they meet a diverting pulley 9, which is rotatably mounted on the counterweight 2. Having passed around the diverting pulley 9, the ropes 3 go again upwards to the traction sheave 7 of the drive machine 6, passing over it along rope grooves. From the traction sheave 7 the ropes go downwards to the elevator car 1, passing under it via the diverting pulleys 4,5 supporting the elevator car 1 on the ropes and continuing upwards to an anchorage 14 in the top part of the shaft, where the other end of the ropes is fixed. The positions of the rope anchorage point 13 in the top part of the shaft, the traction sheave 7 and the diverting pulley 9 supporting the counterweight on the ropes are preferably so aligned with respect to each other that the rope section between the anchorage point 13 and the counterweight 2 as well as the rope section between the counterweight 2 and the traction sheave 7 run substantially in the direction of the path of the counterweight 2. Another advantageous solution is one in which the anchorage 14 in the top part of the shaft, the traction sheave 7 and the diverting pulleys 4,5 supporting the elevator car are so positioned with respect to each other that the rope section going from anchorage 14 to the elevator car 1 and the rope section going from the elevator car 1 to the traction sheave 7 both run in a direction essentially parallel to the path of the elevator car 1. In this case no extra diverting pulleys are needed to direct the passage of the ropes in the shaft. The effect of the rope suspension on the elevator car 1 is substantially centric if the rope pulleys 4 are placed essentially symmetrically with respect to the vertical line passing through the centre of gravity of the elevator car 1.

The machine unit 6 placed above the path of the counterweight 2 is of a flat construction as compared to its width, including the equipment that may be needed for the supply of power to the motor driving the traction sheave 7 as well as the necessary elevator control equipment, both of said equipments 8 being adjoined to the machine unit 6, possibly integrated with it. All essen-

tial parts of the machine unit 6 and the associated equipments 8 are placed between the shaft space needed by the elevator car and/or its overhead extension and a wall of the shaft.

Fig. 2 presents a diagram illustrating the placement of an elevator according to the invention in an elevator shaft 15. The machine unit 6 and possibly also the control panel 8 containing the equipment required for power supply to the motor and for elevator control are fixed to the wall or ceiling of the elevator shaft. The machine unit 6 and the control panel 8 can be mounted at the factory in a single integrated unit which is then installed in the elevator shaft. The elevator shaft 15 is provided with a landing door 17 for each floor, and the elevator car 1 has a car door 18 on the side facing the landing doors. Since the hoisting ropes 3 are passed below the elevator car 1, the machine unit 6 can be placed below the level which the top of the elevator car 1 reaches at the high extremity of its path. In an elevator implemented according to the solution presented, ordinary service operations on the machinery 6 and control panel 8 can be performed while standing on the top of the elevator car 1. Fig. 2 shows in top view how the machine unit 6, traction sheave 7, elevator car 1, counterweight 2 and the guide rails 10 and 11 for the car and counterweight are laid out in the cross-section of the elevator shaft 15. The figure also shows the diverting pulleys 4,5,9 used to suspend the elevator car 1 and counterweight 2 on the hoisting ropes. The hoisting ropes 3 are represented by their cross-sections in the grooves of the rope pulleys 4,5,9 and traction sheave 7.

A preferable drive machinery consists of a gearless machine with an electromotor whose rotor and stator are so mounted that one is immovable with respect to the traction sheave 7 and the other with respect to the frame of the drive machine unit 6.

Another traction sheave elevator according to the invention is presented in Fig. 3 in diagrammatic form. The elevator car 1 and counterweight 2 are suspended on the hoisting ropes 3 of the elevator. The hoisting ropes 3 preferably support the elevator car 1 substantially centrically or symmetrically relative to the vertical line passing via the centre of gravity of the elevator car 1. Similarly, the suspension of the counterweight 2 is preferably substantially centric or symmetrical relative to the vertical line going through the centre of gravity of the counterweight. In Fig. 3, the elevator car 1 is supported by the hoisting ropes 3 by means of diverting pulleys 4,5 provided with rope grooves, and the counterweight 2 is supported by a grooved diverting pulley 9. The diverting pulleys 4 and 5 preferably rotate substantially in the same plane. The hoisting ropes 3 usually consist of several ropes placed side by side, usually at least three ropes. The drive machine unit 6 of the elevator with a traction sheave 7 acting on the hoisting ropes 3 is placed at the top part of the elevator shaft.

The elevator car 1 and the counterweight 2 travel in the elevator shaft along elevator and counterweight guide rails 10,11 which guide them and are placed in

the shaft on the same side relative to the elevator car. The elevator car is suspended on the guide rails in a manner called rucksack suspension, which means that the elevator car 1 and its supporting structures are almost entirely on one side of the plane between the elevator guide rails 10. The elevator and counterweight guide rails 10,11 are implemented as an integrated rail unit 12 having guide surfaces for guiding the elevator car 1 and the counterweight 2. Such a rail unit can be installed faster than separate guide tracks. The elevator and counterweight guides are not shown in the figure. In Fig. 3, the hoisting ropes 3 run as follows: One end of the hoisting ropes is fixed to an anchorage 13 above the path of the counterweight 2 at the top part of the shaft the counterweight 2. From the anchorage 13, the ropes go downwards until they meet a diverting pulley 9 rotatably mounted on the counterweight 2. Having passed around the diverting pulley 9, the ropes 3 go again upwards to the traction sheave 7 of the drive machine 6, passing over it along rope grooves. From the traction sheave 7 the ropes go downwards to the elevator car 1, passing under it via the diverting pulleys 4,5 supporting the elevator car 1 on the ropes and continuing upwards to an anchorage 14 at the top part of the shaft, where the other end of the ropes is fixed. The positions of the rope anchorage point 13 in the top part of the shaft, the traction sheave 7 and the diverting pulley 9 supporting the counterweight on the ropes are preferably so aligned relative to each other that the rope section between the anchorage point 13 and the counterweight 2 as well as the rope section between the counterweight 2 and the traction sheave 7 run substantially in the direction of the path of the counterweight 2. Another advantageous solution is one in which the anchorage 14 in the top part of the shaft, the traction sheave 7 and the diverting pulleys 4,5 supporting the elevator car are so positioned relative to each other that the rope section going from anchorage 14 to the elevator car 1 and the rope section going from the elevator car 1 to the traction sheave 7 both run in a direction essentially parallel to the path of the elevator car 1. In this case no extra diverting pulleys are needed to direct the passage of the ropes in the shaft. The effect of the rope suspension on the elevator car 1 is substantially centric if the rope pulleys 4,5 are placed essentially symmetrically with respect to the vertical midline of the elevator car 1. A suspension arrangement where the ropes go diagonally under the floor of the car provides an advantage regarding elevator lay-out because the vertical portions of the ropes are close to the corners of the car and are therefore not an obstacle e.g. to placing the door on one of the sides of the car 1.

The machine unit 6 placed above the path of the counterweight 2 is of a flat construction as compared to the width of the counterweight, its thickness being preferably at most equal to that of the counterweight, including the equipment that may be needed for the supply of power to the motor driving the traction sheave 7 as well as the necessary elevator control equipment, both of

said equipments 8 being adjoined to the machine unit 6, possibly integrated with it. All essential parts of the machine unit 6 with the associated equipments 8 are within the shaft space extension needed above the shaft space for the counterweight 2, including the safety distance. Outside of this extension may only go some parts inessential to the invention, such as the lugs (not shown in the figures) needed to fix the machinery to the ceiling of the elevator shaft or other structure in the top part of the shaft, or the brake handle. Elevator regulations typically require a 25-mm safety distance from a movable component, but even larger safety distances may be applied because of certain country-specific elevator regulations or for other reasons.

Fig. 4a presents a diagram illustrating the placement of an elevator according to the invention in an elevator shaft 15 as seen from one side. The elevator car 1 and counterweight 2 are suspended in the manner presented in Fig. 3 on the guide rail units 12 and the hoisting ropes 3 (indicated here with a broken line). Near the top of the elevator shaft 15 is a mounting beam 16, to which is fixed a control panel 8 containing the equipment required for power supply to the motor and for elevator control. The mounting beam 16 can be fabricated by fixing the machine unit 6 and the control panel 8 to it at the factory, or the mounting beam can be implemented as part of the frame structure of the machinery, thus forming a 'lug' for fixing the machine unit 6 to the wall or ceiling of the shaft 15. The beam 16 is also provided with an anchorage 13 for at least one end of the hoisting ropes 3. The other end of the hoisting ropes is often fixed to an anchorage 14 located somewhere else except on the mounting beam 16. The elevator shaft 15 is provided with a landing door 17 for each floor, and the elevator car 1 has a car door 18 on the side facing the landing doors. On the topmost floor there is a service hatch 19 opening into the shaft space and so placed that a serviceman can reach the control panel 8 and the machinery 6 through the hatch, if not from the floor then at least from a working platform placed at some height above the floor. The service hatch 19 is so placed and dimensioned that the emergency operation stipulated by elevator regulations can be performed with sufficient ease via the hatch. Ordinary service operations on the machinery 6 and control panel 8 can be performed while standing on the top of the elevator car 1. Fig. 4b presents the elevator of Fig. 3 in top view, showing how the guide rail units 12, counterweight 2 and elevator car 1 are placed in the cross-section of the elevator shaft 15. The figure also shows the diverting pulleys 4,5,9 used to suspend the elevator car 1 and counterweight 2 on the hoisting ropes 3. In Fig. 4b, the guide rail lines 10,11 for the elevator car and counterweight are essentially in the same plane between the elevator car and the counterweight with the rail ridges placed in the direction of this plane.

A preferable drive machinery consists of a gearless machine with an electromotor whose rotor and stator are so mounted that one is immovable with respect to

the traction sheave 7 and the other with respect to the frame of the drive machine unit 6. Often the essential parts of the motor are preferably inside the rim of the traction sheave. The action of the operating brake of the elevator is applied to the traction sheave. In this case the operating brake is preferably integrated with the motor. In practical applications, the solution of the invention regarding the machinery means a maximum thickness of 20 cm for small elevators and 30-40 cm or more for large elevators with a high hoisting capacity.

The hoisting machine unit 6 employed in the invention, together with the motor, can be of a very flat construction. For example, in an elevator with a load capacity of 800 kg, the rotor of the motor of the invention has a diameter of 800 mm and the minimum thickness of the whole hoisting machine unit is only about 160 mm. Thus, the hoisting machine unit used in the invention can be easily accommodated in the space according to the extension of the counterweight path. The large diameter of the motor involves the advantage that a gear system is not necessarily needed.

Fig. 5 presents a cross-section of the hoisting machine unit 6, showing the elevator motor 126 in top view. The motor 126 is implemented as a structure suitable for a drive machine unit 6 by making the motor 126 from parts usually called endshields and an element 111 supporting the stator and at the same time forming a side plate of the hoisting machine unit. The side plate 111 thus constitutes a frame part transmitting the load of the motor and at the same time the load of the hoisting machine unit. The unit has two supporting elements or side plates, 111 and 112, which are connected by an axle 113. Attached to side plate 111 is the stator 114 with a stator winding 115 on it. Alternatively, side plate 111 and the stator 114 can be integrated into a single structure. The rotor 117 is mounted on the axle 113 by means of a bearing 116. The traction sheave 7 on the outer surface of the rotor 117 is provided with five rope grooves 119. Each one of the five ropes 102 goes about once around the traction sheave. The traction sheave 7 may be a separate cylindrical body placed around the rotor 117, or the rope grooves of the traction sheave 7 may be made directly on the outer surface of the rotor as shown in Fig. 5. The rotor winding 120 is placed on the inner surface of the rotor. Between the stator 114 and the rotor 117 is a brake 121 consisting of brake plates 122 and 123 attached to the stator and a brake disc 124 rotating with the rotor. The axle 113 is fixed to the stator, but alternatively it could be fixed to the rotor, in which case the bearing would be between the rotor 117 and side plate 111 or both side plates 111 and 112. Side plate 112 acts as an additional reinforcement and stiffener for the motor/hoisting machine unit. The horizontal axle 113 is fixed to opposite points on the two side plates 111 and 112. Together with connecting pieces 125, the side plates form a boxlike structure.

Fig. 6 presents a cross-section of another hoisting machine unit 6 applied in the invention. The machine unit 6 and the motor 326 are shown in side view. The

machine unit 6 and motor 326 form an integrated structure. The motor 326 is substantially placed inside the machine unit 6. The stator 314 and the axle 313 of the motor are attached to the side plates 311 and 312 of the machine unit. Thus the side plates 311 and 312 of the machine unit also form the endshields of the motor, at the same time acting as frame parts transmitting the load of the motor and machine unit.

Fixed between the side plates 311 and 312 are sustainers 325 which also act as additional stiffeners of the machine unit.

The rotor 317 is rotatably mounted on the axle 313 with a bearing 316. The rotor is of a disc-shaped design and is placed in the axial direction essentially at the middle of the axle 313. Placed on either side of the rotor, between the windings and the axle, are two circular halves 318a and 318b of the traction sheave 318, both having the same diameter. Each half of the traction sheave carries the same number of ropes 302.

The diameter of the traction sheave is smaller than that of the stator or rotor. The traction sheave being attached to the rotor, it is possible to use traction sheaves of different diameters with the same rotor diameter. Such variation provides the same advantage as the use of a gear system, and this is another advantage achieved by applying this kind of a motor in the invention. The traction sheave is fixed to the rotor disc in a manner known in itself, e.g. by means of screws. Of course, the two halves of the traction sheave 318 can alternatively be integrated with the rotor to form a single body.

Each one of the four ropes 302 runs over the traction sheave along its own groove. For the sake of clarity, the ropes are only shown as sections on the traction sheave.

The stator 314 together with the stator winding 315 forms a U-shaped sector or segmented sector resembling a clutching hand over the outer edge of the rotor, with the open side of the U-shape towards the ropes. The largest sector width possible in the structure depends on the relation of the inner diameter of the stator 314 and the diameter of the traction sheave 318. In practical solutions, an advantageous relationship of the magnitudes of these diameters is such that a sector diameter of 240 degrees is not exceeded. However, if the hoisting ropes 302 are brought closer to the vertical line passing through the axle 313 of the machine by providing the machine with diverting pulleys, the arrangement will easily allow the use of a sector of 240-300 degrees, depending on the position of the diverting pulleys below the motor. At the same time, the angle of contact of the ropes on the traction sheave is increased, improving the frictional grip of the traction sheave. Between the stator 314 and the rotor 317 are two air gaps α substantially perpendicular to the axle 313 of the motor.

If necessary, the hoisting machine unit can also be provided with a brake, which is placed e.g. inside the traction sheave between the side plates 311,312 and

the rotor 317.

It is obvious to a person skilled in the art that different embodiments of the invention are not restricted to the examples described above, but that they may instead be varied within the scope of the claims presented below. For example, the number of times the hoisting ropes are passed between the top part of the elevator shaft and the counterweight or elevator car is not very decisive with regard to the basic advantages of the invention, although it is possible to achieve some additional advantages by using multiple rope stretches. In general, applications should be so designed that the ropes go to the elevator car at most as many times as to the counterweight.

In suspension arrangements where the path of the counterweight is shorter than that of the car, a somewhat shorter shaft length requirement is achieved by placing the machinery above the path of the counterweight than in suspension arrangements where the paths of the car and counterweight have equal lengths.

Furthermore, it is obvious to the skilled person that the larger machine size needed for elevators designed for heavy loads can be achieved by increasing the diameter of the electromotor, without substantially increasing the thickness of the machinery.

It is also obvious to the skilled person that the elevator car, counterweight and machine unit can be laid out in the cross-section of the elevator shaft in a way differing from the above examples. A possible different layout is one in which the machinery and counterweight are behind the car as seen from the shaft door and the ropes are passed under the car diagonally with respect to the bottom of the car. Passing the ropes diagonally or otherwise obliquely with respect to the shape of the car bottom is an advantageous solution which can be used in other types of suspension lay-outs as well to ensure that the car is symmetrically suspended on the ropes with respect to the center of mass of the elevator.

Furthermore, it is obvious to the skilled person that the equipment required for the supply of power to the motor and the equipment needed for the control of the elevator can be placed elsewhere except in conjunction with the machine unit, e.g. in a separate control panel. Similarly, it is obvious that an elevator implemented according to the invention can be equipped in a way differing from the examples presented. For instance, instead of an automatic door solution, the elevator could be equipped with a turn door.

Claims

1. Traction sheave elevator comprising an elevator car (1) moving along elevator guide rails (10), a counterweight (2) moving along counterweight guide rails (11), a set of hoisting ropes (3) on which the elevator car and the counterweight are suspended, and a drive machine unit (6) comprising a traction sheave (7) driven by the drive machine and engaging the hoisting ropes (3), wherein the drive

machine unit (6) of the elevator is placed in the top part of the elevator shaft (15) in the space between the shaft space needed by the elevator car on its path and/or the overhead extension of the shaft space needed by the elevator car and a wall of the elevator shaft (15).

characterized in that the hoisting ropes are passed under the elevator car by means of diverting pulleys, and that the elevator motor has a discoidal rotor (117,317) and/or that the machine unit (6) is of a flat construction type and/or that the drive machine unit (6) is gearless.

2. Traction sheave elevator according to one of the preceding claims, characterized in that when the elevator car (1) is at the high extremity of its path, its top part reaches at least the level of the bottom edge of the drive machine unit (6).
3. Traction sheave elevator according to one of the preceding claims, characterized in that in the thickness-wise direction of the counterweight, the drive machine unit (6) is placed substantially inside of the overhead shaft space extension needed for the counterweight (2), including the safety distance.
4. Traction sheave elevator according to one of the preceding claims, characterized in that the drive machine unit (6) is completely inside the shaft space extension required by the counterweight (2) on its path, including the safety distance, and that joint to the drive machine unit (6) is a control panel (8) containing the equipment required for the supply of power to the motor (126, 326) driving the traction sheave (7), that control panel being preferably integrated with the drive machine unit (6).
5. Traction sheave elevator according to anyone of the preceding claims, characterized in that the drive machine unit (6) has a thickness not exceeding that of the counterweight (2).
6. Traction sheave elevator according to anyone of the preceding claims, characterized in that the drive machine unit (6) is fixed in the elevator shaft (15) to a wall of the shaft.
7. Traction sheave elevator according to anyone of the preceding claims, characterized in that the drive machine unit (6) is fixed in the elevator shaft (15) to the ceiling of the shaft.
8. Traction sheave elevator according to anyone of the preceding claims,

characterized in that the suspension of the elevator car (1) and counterweight (2) on the hoisting ropes (3) is so fitted that the path of the counterweight is shorter than that of the elevator car.

9. Traction sheave elevator according to anyone of the preceding claims, characterized in that the hoisting ropes (3) are passed under the elevator car (1) over two diverting pulleys (4,5) preferably so that they pass under the floor of the elevator car (1) via a point directly below the center of mass of the elevator car.

10. Traction sheave elevator according to anyone of the preceding claims, characterized in that the hoisting ropes (3) are passed under the elevator car (1) via two diverting pulleys (4,5) preferably passing diagonally under the floor of the elevator car (1).

11. Traction sheave elevator according to anyone of the preceding claims 1 to 8, characterized in that the elevator car (1) is suspended using rucksack-type suspension and that the guide rails (10,11) for the car (1) and counterweight (2) are on the same side of the car (1), preferably with the counterweight guide rail (11) and the elevator guide rail (10) integrated into a guide rail unit (12) provided with guide surfaces for both the counterweight (2) and the car (1).

Patentansprüche

1. Antriebsscheibenaufzug mit einer Aufzugskabine (1), die sich entlang von Aufzugsführungsschienen (10) bewegt, einem Gegengewicht (2), das sich entlang von Gegengewichtsführungsschienen (11) bewegt, einem Satz von Hubschienen (3), an denen die Aufzugskabine und das Gegengewicht aufgehängt sind, und einer Antriebsmaschineneinheit (6), die eine Antriebsscheibe (7) umfaßt, die durch die Antriebsmaschine angetrieben wird und mit den Hubschienen (3) zusammenwirkt, wobei die Antriebsmaschineneinheit (6) des Aufzugs im obersten Teil des Aufzugsschachts (15) angeordnet ist im Bereich zwischen dem Schachtraum, der von der Aufzugskabine auf ihrem Weg benötigt wird und/oder der oberen Verlängerung dieses Schachtbereichs und einer Wand des Aufzugsschachtes (15), **dadurch gekennzeichnet**, daß die Hubschienen über Umlenkrollen (4, 5) unter der Aufzugskabine (1) entlanggeführt sind, und daß der Aufzugsmotor einen scheibenförmigen Rotor (117,317) und/oder eine flache Maschineneinheit (6) und/oder eine getriebelose Antriebsmaschineneinheit (6) aufweist.

2. Antriebsscheibenaufzug nach Anspruch 1, **dadurch gekennzeichnet**, daß wenn sich die Auf-

zugskabine (1) am höchsten Punkt ihres Weges befindet, ihr oberstes Teil mindestens die Höhe der unteren Kante der Antriebsmaschineneinheit (6) erreicht.

3. Antriebsscheibenaufzug nach einem der vorhergehenden Ansprüche, **dadurch gekennzeichnet**, daß die Antriebsmaschineneinheit (6) in der Richtung der Dicke des Gegengewichts im wesentlichen innerhalb der oberen Erstreckung des Schachtraums für das Gegengewicht (2), einschließlich der Sicherheitsdistanz, angeordnet ist.

4. Antriebsscheibenaufzug nach einem der vorhergehenden Ansprüche, **dadurch gekennzeichnet**, daß sich die Antriebsmaschineneinheit (6) vollständig innerhalb der Schachtraumerweiterung, die vom Gegengewicht (2) auf dessen Weg benötigt wird, einschließlich der Sicherheitsdistanz, befindet, und daß mit der Antriebsmaschine (6) eine Steuertafel (8) verbunden ist, die die Ausrüstung für die Energieversorgung des Motors (126, 326), der die Antriebsscheibe (7) antreibt, enthält, wobei die Steuertafel vorzugsweise in die Antriebsmaschineneinheit (6) integriert ist.

5. Antriebsscheibenaufzug nach einem der vorhergehenden Ansprüche, **dadurch gekennzeichnet**, daß die Antriebsmaschineneinheit (6) eine Dicke aufweist, die die des Gegengewichts (2) nicht übersteigt.

6. Antriebsscheibenaufzug nach einem der vorhergehenden Ansprüche, **dadurch gekennzeichnet**, daß die Antriebsmaschineneinheit (6) im Aufzugsschacht (15) an einer Wand des Schachtes befestigt ist.

7. Antriebsscheibenaufzug nach einem der vorhergehenden Ansprüche, **dadurch gekennzeichnet**, daß die Antriebsscheibe (6) im Aufzugsschacht (15) an der Decke des Schachtes befestigt ist.

8. Antriebsscheibenaufzug nach einem der vorhergehenden Ansprüche, **dadurch gekennzeichnet**, daß die Aufhängung der Aufzugskabine (1) und des Gegengewichts (2) an den Hubschienen (3) so vorgenommen ist, daß der Weg des Gegengewichts kürzer ist als der der Aufzugskabine.

9. Antriebsscheibenaufzug nach einem der vorhergehenden Ansprüche, **dadurch gekennzeichnet**, daß die Hubschienen (3) unter der Aufzugskabine (1) über zwei Umlenkrollen (4, 5) vorzugsweise so geführt sind, daß sie unter dem Boden der Aufzugskabine (1) direkt unter dem Schwerpunkt der Aufzugskabine verlaufen.

10. Antriebsseilenaufzug nach einem der vorhergehenden Ansprüche, **dadurch gekennzeichnet**, daß die Hubseile (3) über zwei Umlenkrollen (4, 5) unter die Aufzugskabine (1) und vorzugsweise diagonal unter dem Boden der Aufzugskabine (1) geführt sind.

11. Antriebsseilenaufzug nach einem der vorhergehenden Ansprüche 1 bis 8, **dadurch gekennzeichnet**, daß die Aufzugskabine (1) unter Verwendung einer Aufhängung des Rucksacktyps aufgehängt ist, und daß die Führungsschienen (10, 11) für die Aufzugskabine (1) und das Gegengewicht (2) sich auf der gleichen Seite der Aufzugskabine (1) befinden, wobei die Gegengewichtsführungsschiene (11) und die Aufzugsführungsschiene (10) vorzugsweise in einer Führungsschieneinheit (12) integriert sind, die mit Führungsoberflächen sowohl für das Gegengewicht (2) als auch für die Aufzugskabine (1) versehen ist.

Revendications

1. Ascenseur à poulie de traction comprenant une cabine d'ascenseur (1) qui se déplace le long de rails de guidage d'ascenseur (10), un contrepoids (2) qui se déplace le long de rails de guidage de contrepoids (11), un ensemble de câbles de levage (3) sur lesquels la cabine d'ascenseur et le contrepoids sont suspendus, et une machine d'entraînement (6) qui comporte une poulie de traction (7) entraînée par la machine d'entraînement et en prise avec les câbles de levage (3), la machine d'entraînement (6) de l'ascenseur est placée dans la partie supérieure de la cage d'ascenseur (15) dans l'espace compris entre l'espace de cage nécessaire à la cabine d'ascenseur sur son parcours et/ou le prolongement supérieur de ce parcours et un mur de la cage d'ascenseur (15), caractérisé en ce que les câbles des levage (3) passent sous la cabine d'ascenseur (1) autour de poulies de renvoi (4,5) sous le plancher de la cabine d'ascenseur (1), et la machine d'entraînement comprend un rotor en forme de disque (117,317) et/ou la machine d'entraînement (6) est de construction plate et/ou la machine d'entraînement (6) est sans engrenages.
2. Ascenseur à poulie de traction suivant la revendication 1, caractérisé en ce que, lorsque la cabine d'ascenseur (1) se trouve à l'extrémité supérieure de son parcours, sa partie supérieure atteint au moins le niveau du bord inférieur de la machine d'entraînement (6).
3. Ascenseur à poulie de traction suivant une quelconque des revendications précédentes, caractérisé en ce que, dans le sens de l'épaisseur du contrepoids, la machine d'entraînement (6) est pla-

cée sensiblement à l'intérieur du prolongement supérieur de l'espace de cage nécessaire au contrepoids (2), y compris la distance de sécurité.

4. Ascenseur à poulie de traction suivant une quelconque des revendications précédentes, caractérisé en ce que la machine d'entraînement (6) est complètement à l'intérieur du prolongement de l'espace de cage requis par le contrepoids (2) sur son chemin, y compris la distance de sécurité, et en ce qu'un tableau de commande (8), contenant l'équipement requis pour l'alimentation en énergie du moteur (126,326) d'entraînement de la poulie de traction (7) est adjoint à la machine d'entraînement (6), ledit tableau de commande étant de préférence intégré à la machine d'entraînement (6).
5. Ascenseur à poulie de traction suivant une quelconque des revendications précédentes, caractérisé en ce que l'épaisseur de la machine d'entraînement (6) ne dépasse pas celle du contrepoids (2).
6. Ascenseur à poulie de traction suivant une quelconque des revendications précédentes, caractérisé en ce que la machine d'entraînement (6) est fixée dans la cage d'ascenseur (15) à une paroi de la cage.
7. Ascenseur à poulie de traction suivant une quelconque des revendications précédentes 1 à 7, caractérisé en ce que la machine d'entraînement (6) est fixée dans la cage d'ascenseur (15) au plafond de la cage.
8. Ascenseur à poulie de traction suivant une quelconque des revendications précédentes, caractérisé en ce que la suspension de la cabine d'ascenseur (1) et du contrepoids (2) sur les câbles de levage (3) est agencée de sorte que le parcours du contrepoids est plus court que celui de la cabine d'ascenseur.
9. Ascenseur à poulie de traction suivant une quelconque des revendications précédentes, caractérisé en ce que les câbles de levage (3) passent sous la cabine d'ascenseur (1) autour de deux poulies de renvoi (4,5), de préférence d'une manière telle qu'ils passent sous le plancher de la cabine d'ascenseur (1) via un point situé directement au-dessous du centre de gravité de la cabine d'ascenseur.
10. Ascenseur à poulie de traction suivant une quelconque des revendications précédentes, caractérisé en ce que les câbles de levage (3) passent sous la cabine d'ascenseur (1) via deux poulies de renvoi (4,5), et ils passent de préférence en diagonale sous le plancher de la cabine d'ascenseur (1).

11. Ascenseur à poulie de traction suivant une quelconque des revendications précédentes, caractérisé en ce que la cabine d'ascenseur (1) est suspendue au moyen d'une suspension du type sac à dos, et en ce que les rails de guidage (10,11) pour la cabine (1) et le contrepoids (2) sont du même côté de la cabine (1), de préférence avec le rail de guidage de contrepoids (11) et le rail de guidage d'ascenseur (10) intégrés en un rail de guidage unitaire (12) présentant des surfaces de guidage à la fois pour le contrepoids (2) et pour la cabine (1).

15

20

25

30

35

40

45

50

55




Fig. 1




Fig. 2




Fig. 3




Fig. 4a




Fig. 4b




Fig. 5




Fig.6